



specialty lubricants



Quality is in our nature

Eurol Grease CS-2/102 FD

Synthetic grease / anti corrosion agent for the food industry

Description:

Eurol Grease CS-2 / 102 FD with Eurol SYNGIS Technology is a synthetic high performance lubricating grease developed for extreme situations in the food processing and pharmaceutical industry.

Eurol Grease CS-2 / 102 FD is suitable for lubrication of:

- Open and closed bearings
- Cables and chains
- Autoclaves
- Steam valves
- Agricultural and fishing equipment
- Equipment working in extreme environments like (salt) water and high temperatures

Instructions for use:

- Clean the system thoroughly with Eurol Swift Clean 120 FD Spray
- Suitable for automatic lubrication systems

Eurol Grease CS-2/102 FD has the following characteristics:

- InS H1, 1796871
- Excellent anti wear and EP properties
- Extreme protection against corrosion
- Shear stable
- Excellent water resistancy
- Resistant to shock loads
- Oxidation stable
- Less oil bleeding, so very suitable for automatic lubrication systems
- Economical in use

Physical properties:

Colour	Light brown	
NLGI Consistency	2	ASTM D 217
Thickener type	Calcium Sulfonate	
Base Oil Viscosity at 40°C	400 cSt	ASTM D 445
Base Oil Type	Synthetic	
Operating temperature	-40 - 175 °C	

Greases - S005118
Version 1.0, 09-10-2015

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurolspecialty.com